

TECHNICAL DETAILS OF THE VERSION “QUADROWINGS SUPERSAFE®”

PATENTED DESIGN IMPROVEMENTS:


1. Double lock system
2. **Enhanced anti-tampering feature with a safety ribs that cover the lid edge.**
3. Tear-off band
4. “Quadro-Wings®” for easy opening
5. Improved sealing geometry, ensuring no leakage even after removal of the tear-off band
6. Total leak-proof performance
7. Flat inner surface, suitable for master batch shaking
8. Improved stacking of filled buckets
9. Optimized lid stacking

TESTS ON QUADROWINGS SUPERSAFE®

19/20 LT BUCKET 650 GR PP COPO MFI 12
19/20 LT LID 170 GR PP COPO MFI 12


FREE FALL: IMPACT OF ASSEMBLED PAIL / CLOSURE ON THE SURFACE PLANE:

Free fall at 1.50 meter height. Position of the pail vertical.



Results:
No rupture exhibited on the closure.
No breakage evident.
No Leakage

Free fall at 1.00 meter height. Position of the pail inverted (on the closure).




Results:
No rupture exhibited on the closure.
No breakage evident.
No Leakage.

Free fall at 1.50 meter height. Position of the pail at 45°.



Results:
No rupture exhibited on the closure.
No breakage evident.
No Leakage.

Free fall at 1.00 meter height. Position of the pail Horizontal.



Results:
No rupture exhibited on the closure.
No breakage evident.
No Leakage.




ABATE BASILIO
MOULDS FOR PACKAGING

50
YEARS OF INNOVATION



HERMETIC LEAK TEST:

Pail positioned horizontal for 24 hours.



Results:
No escape of water.
No Leakage.